



GLADIO SMALL BORE

ANCIENT ROOTS.

Our tribute to the weapon of the ancient Rome that conquered the world known until then wears today a brand-new look: Victrix Small Bore breaks through the borders and conquer new and uncharted territories.

 **VICTRIX**
A R M A M E N T S



GLADIO SB DATA SHEET

Destination use

Sporting
Military training

Caliber / Twist rate

.22 L.R. (1/16)

Barrel length

22"
24"
26"

Weight

5,95 kg (13.12 lb) with an empty magazine, barrel length 22" and no scope
6,08 kg (13.40 lb) with an empty magazine, barrel length 24" and no scope
6,20 kg (13.67 lb) with an empty magazine, barrel length 26" and no scope

Dimension

Closed overall length: 804 mm (31.65")
Open overall length: 1050 mm (41.33")
With muzzle thread protector and barrel length 22"

Closed overall length: 854 mm (33.62")
Open overall length: 1100 mm (43.30")
With muzzle thread protector and barrel length 24"

Closed overall length: 906 mm (35.66")
Open overall length: 1152 mm (45.35")
With muzzle thread protector and barrel length 26"

Base rifle

Barrel in special steel
Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine adjustment, and an insulated cheek piece
Single feed and single stack 10-round magazine
Reversible EVO button folding system
Octagonal elliptic forend with attachment system for accessories, a 20 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913
Ergonomic and interchangeable zero angle flat top grip for standard AR platform
20 MoA removable action rail according to STANAG 4694/Mil std 1913
Muzzle thread protector
Detachable multifunction carry handle with quick mount:
· With QM (Quick mount) attachment for picatinny rail
· Ergonomic handle
· Integrated picatinny rail
· Hook for rope attachment
· QD (Quick detach) attachments
· Tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads
· Front magnetic bit holder for field maintenance
Action in AISI 630 worked out from billet
Bolt with two asymmetric rear lugs arranged at an angle of 60-degree lift, with a quick disassembly system, a double extractor and an ergonomic interchangeable bolt lever
PVD finish on the action and on the bolt
Victrix Sporting Plus adjustable single stage trigger with a two-position safety: standard setting approx. 250 gr (8.82 oz)
Heavy-duty reinforced transport case
User manual and welcome kit

Stock colour

CERAKOTE ceramic polymer firearm coatings available in:

Dark Grey
Dark Olive Drab Green
Medium Flat Brown
Armor Black

Optional

Side picatinny rails for forend with attachment system for accessories according to STANAG 4694/Mil std 1913
45 MoA action rail according to STANAG 4694/Mil std 1913

In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.



VICTRIX
SMALL BORE