



Kinetic

CALIBER / TWIST RATE

308 Win Match (1/10 - 1/11)
 6.5 Creedmoor (1/7,5)
 6 Creedmoor (1/8)
 6 XC (1/8)
 22 LR (1/16)

BARREL LENGTH

27" (Centerfire)
 22" (Rimfire)

WEIGHT

8,80 kg (19.40 lb) with a magazine and no scope (Centerfire)
 7,85 kg (17.30 lb) with a magazine and no scope (Rimfire)

DIMENSION

Closed overall length: 998 mm (39.29")
 Open overall length: 1245 mm (49.02")
 with muzzle brake and barrel length 27"

Closed overall length: 805 mm (31.69")
 Open overall length: 1052 mm (41.42")
 with muzzle brake and barrel length 22"

FINISH

Natural finish with clear protective coating

CONFIGURATION

Match-grade lapped barrel with heavy contour
 Buttstock with horizontal and vertical multiple button adjustments and an adjustable insulated cheek piece, equipped with a removable lower slider
 Reversible EVO button folding system
 High strength monobloc chassis in light alloy, with accessory attachment system, adjustable thumb rest, and integrated barricade stop
 Upgraded lightweight alloy forend with lateral accessory attachment system and an integrated full-length central Anschutz-type lower rail with ARCA rail
 Handguard cover on the front with a Picatinny rail L=420 mm (16.54")
 Nr. 4 lateral forend weights (250 g each) with a quick-release system
 Ergonomic and interchangeable zero angle flat top grip for standard AR platform
 20 MoA removable rail in light alloy
 PVD surface coating on action and bolt
 Transport case
 User manual and welcome kit


Unless otherwise stated in writing, only configuration and equipment listed specifically listed are included; any accessory not explicitly mentioned is excluded.

Centerfire

Single feed and double stack 10-round metal magazine
 Victrix Kinetic muzzle brake
 Short action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge machine
 Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position equipped with longitudinal grooves and an interchangeable bolt lever
 Victrix Sporting Plus adjustable single stage trigger with a two-position safety: standard setting approx. 400 gr (14.11oz)

Rimfire

10-round single-stack polymer magazine
 Muzzle thread protector
 Action in AISI 630 worked out from billet through milling and turning with finish on grinding machinery
 One-piece bolt with two asymmetric rear lugs, with a quick disassembly system, a double extractor and an ergonomic interchangeable bolt lever
 Victrix Sporting Plus adjustable single stage trigger with a two-position safety: standard setting approx. 250 gr (8.82 oz)



In caso di discrepanze tra immagini e dati, prevaleggono le specifiche tecniche del sito ufficiale.



Kinetic

Centerfire - RH




Centerfire - LH



Rimfire - RH



Rimfire - LH



*In caso di discrepanze tra immagini e dati,
prevolgono le specifiche tecniche del sito ufficiale.*